

CT Series

Functional features Multi-purpose usage

CT SERIES – HATCHERS



CT60h



CT90h



CT120h

Egg Hatching Capacity			
	CT60h	CT90h	CT120h
Hen	48	72	96
Quail	160	240	320
Turkey	40	60	80
Partridge	120	180	240
Pheasant	96	144	192
Duck	40	60	80
Goose	24	36	48



CT Series Hatchers

CT Series hatcher type models with **CS24** hatchery baskets can be used as a hatcher for last period of incubation in conjunction with a automatic setter type incubator or they can be used for all incubation period by turning the eggs by hand.



CS24 - hatchery baskets with their separated parts provide you hatching of different type of eggs in different baskets.



CS24 - hatchery baskets fits exactly to the tiers of the models. They have 4 mini baskets. These baskets can be used together or partially with the base carrying baskets. Also, All hatcher models like the other CT series incubators come up with 2 pieces water pan with 3 division and **Prodi Wet Bulb Temperature** to observe and control humidity.



CLS Cabinet panels provide **high temperature insulation** and protect your eggs against electricity cutoffs for a long time. Temperature control is fully digital and more precise with **PID parameters**, which also ensures minimum energy consumptions.




CT Series Hatchers

Digital controller




power fuse light

Adjustable air vent



Basket tiers



Features	
Egg capacity	CT60h : 48 chicken eggs hatching capacity CT90h : 72 chicken eggs hatching capacity CT120h : 96 chicken eggs hatching capacity
Accessories	CT60h : (2 x CS24) CT90h : (3 x CS24) CT120h : (4 x CS24)
Power	220/230 Volt – 50 / 60 HZ. Power: CT60h: avr.: 50w max: 145W CT90h: avr.: 55w max: 145W CT120h: avr.: 60w max: 145W
Cabinet	High insulation CLS panels Double-glazed window in door with full sight 2.service door in backside
Ventilation	Airroute - perfect laminar flow, Forced ventilation with unique fan Adjustable air outlet vent for controlling of air current
Temperature	PID- Digital temperature control Electronic temperature sensor Digital temperature display(0,1 decimal), Stainless heaters Digital calibration property
Humidity	2 pieces water pan with 3 division for humidification Wet Bulb Thermometer (assembled in door window)
Light	Inside light with on- off button in control panel
Others	Fully assembled, no need for montage Safety fuses

We reserve the right to change specifications due to our policy of improvement.

Product Pages:

CT60h : www.kulucka.com/eng/ct60h.html

CT90h : www.kulucka.com/eng/ct90h.html

CT120h : www.kulucka.com/eng/ct120h.html

